

calibration kit for analogue test gauge

TGK A

REV. 05 E 02 / 07

IN ORDER TO IMPROVE THEIR PRODUCTION, MESSRS. NUOVA FIMA RESERVE THE RIGHT TO THEMSELVES TO MAKE ALL THE MODIFICATIONS THAT THEY DEEM INDISPENSABLE AT ANY TIME. UPDATED DATA-SHEETS ARE AVAILABLE ON SITE: www.nuovafima.com

Pneumatic pump

Generating pressure and vacuum

*pressure: up to 500 *psi* (35 bar)

*vacuum: up to -28 *inHg* (-0,950 bar).

Hydraulic pump

Generating pressure up to 15000 *psi* (1000 bar).



Portable kit in combination with the test pressure gauges of our catalogue section 1.
Designed to allow the end user to calibrate the control instruments on field that normally have to be done to the laboratory.

pneumatic Kit:

- Pneumatic hand held pump (see LPP or LTP data sheet).
- Set of 6 pieces BSP and NPT adaptors.
- Set of seals.
- Rigid plastic carrying case with foam.
- Manuals.

hydraulic Kit:

- Hydraulic hand held pump (see HTP data sheet).
- Hydraulic hose, quick connection PN 1000.
- Set of 6 pieces BSP and NPT adaptors.
- Set of seals.
- Rigid plastic carrying case with foam.
- Manuals

CONBINABLE INSTRUMENTS

PRESSURE GAUGES DS 4" (100 mm)

Ranges: from 15 (1) to 15000 *psi* (1000 bar).

Accuracy: $\pm 1\%$ VFS / $\pm 1,6\%$ VFS.

Functional and constructive characteristics:
see data sheets section 1.

PRESSURE GAUGES DS 6" (150 mm)*

Ranges: from 15 (1) to 15000 *psi* (1000 bar).

Accuracy: $\pm 1\%$ VFS

Functional and constructive characteristics:
see data sheets section 1.

PRESSURE GAUGE MN 15/16/17*

Ranges: from 15 (1) to 15000 *psi* (1000 bar).

Accuracy: $\pm 0,25\%$ VFS / $\pm 0,6\%$ VFS.

Functional and constructive characteristics:
see data sheet MN15/16/17

*Suitable for hydraulic version only

"HOW TO ORDER" SEQUENCE

Section / Model / Version / Range

